



# *Our Authentic Clay Tile Fires The Imagination*

## **THE OLD-WORLD STANDARD FOR TODAY**


Our rigid adherence to ageless tradition has made US Tile the most trusted name for authentic clay roof tile in America. Our inspired pallet of all-natural, kiln-fired earthen hues has been specified by leading architects and designers for over 35 years. As Americas' largest clay tile manufacturer, US Tile also leads the industry in innovation, from lightweight products designed for the reroof market, to our 100% recyclable, environmentally friendly cool roofs.

*US Tile, the Old-World standard for today's innovative roofing designs.*





## *Two-Piece Mission*



First appearing in the Bronze Age, on the temple roofs of kings and refined through fire-baking by the ancient Greeks, two-piece clay tile has been the ultimate roofing product for millennia. Our highly refined modern manufacturing techniques have enabled US Tile to improve on the ageless tradition and style of traditional two-piece clay tile design, and deliver color fast, durable products that will last a lifetime.





## *One-Piece S Tile*



The modern design of our one-piece S Mission Tile combines the cap and pan of a two-piece system into a single piece, delivering the same traditional aesthetics using fewer tiles, saving cost and installation time. Made from the same natural clays and kiln-fired colors, our Mission S Tile products are true to their roots, allowing custom roofscape options such as boosting, while maintaining the rich beauty and durability of clay at a substantially lower price.



## *ClayLite®*



Our "S" Style ClayLite® product line embodies the innovation that has become synonymous with US Tile. Designed specifically for the reroof market, our unique lightweight ClayLite products weigh less than 600 pounds per square, and do not typically require structural reinforcement. Made from the same materials and processes as our traditional clay roofing products, ClayLite offers the superior performance, aesthetics, and kiln-fired color pallets with as much as 40% less weight.



## *Pro Shake Plus®*



ProShake Plus® combines the aesthetics of a traditional wood shake roof with the superior performance, durability, color fastness, Class "A" fire rating, and life of natural clay. Backed by an unsurpassed transferable lifetime limited warranty with additional no-fade protection, ProShake Plus can be installed anywhere without concern for freeze-thaw conditions, salt intrusion, or attacks by insects. ProShake Plus delivers the aesthetics of a wood shake roof with the features and benefits only true clay products can offer.



**US TILE MANUFACTURES CLAY ROOFING TILE IN VARIOUS STYLES, TEXTURES AND COLORS.**



| PRODUCT         | WIDTH   | LENGTH | PIECES PER SQUARE | WEIGHT PER SQUARE |
|-----------------|---------|--------|-------------------|-------------------|
| 2-Piece Mission | 7"-8.5" | 18"    | 172               | 1,000 lbs         |
| 1-Piece S Tile  | 13"     | 18"    | 88                | 800 lbs           |
| ClayLite®       | 13"     | 18"    | 88                | 590 lbs           |
| ProShake Plus®  | 8.5"    | 14"    | 154               | 590 lbs           |

*Architect Information*



**Basic Use**

US Tile clay roofing tiles are applied on sloped roofs where aesthetics, longevity and low life cycle costs are major considerations.

**Composition and Materials**

US Tile products are manufactured from various clays and kiln-fired. US Tile products are available in standard earth tones and authentic kiln-flashed colors.

**Warranty**

US Tile products (sold in the United States) are covered by US Tile’s Transferable Lifetime Limited Warranty\* that includes coverage against fading.

**Limitations**

The standard roof pitch for US Tile Mission profile products is 3:12 (25%). Roof slopes below 3:12 (25%) require an approved waterproofing system. The minimum roof pitch for ProShake Plus is 4:12 (33%). Standard US Tile Mission profile products are not recommended for climate zones that experience repeated freeze-thaw cycling. ProShake Plus products and Grade 1 certified Mission profile products meet the requirements of ASTM C 1167-96 and can be installed in areas with severe weather conditions.

**Installation Recommendations**

Please refer to the Installation Manual for Moderate Climate Regions published by the Roof Tile Institute.

**Technical Data**

US Tile Products – ICBO # 3523 • ProShake Plus® Products conform to ASTM C1167-96 for ICBO #1273

\*Please refer to US Tile’s Transferable Lifetime Limited Warranty for details.



Colors depicted may vary from actual colors due to the inherent variations in natural clay products and the limitations of the lithographic printing process. The concerned parties should examine actual color samples, at both the time of initial color selection and once again from the delivered production run prior to installation.

In order to avoid any possible unwanted color patterning during the installation of blended colors, the skilled installer should periodically view the roof from ground level at a distance of about 50 feet. This procedure will help ensure the desired random look, and help to avoid "hot spots", checkerboarding, streaks or stairstepping. Acceptable blending cannot be done at the factory or on the ground. It can only be done as the product is installed.